

ASL – Fall 2016

Gitlab, SW setup + Bash

Gitlab account and permissions

Create a repository

Sign in - GitLab - Mozilla Firefox marks Tools Help

https://gitlab.inf.ethz.ch

You need to sign in or sign up before continuing.

GitLab Community Edition

Open source software to collaborate on code

Manage git repositories with fine grained access controls that keep your code secure. Perform code reviews and enhance collaboration with merge requests. Each project can also have an issue tracker and a wiki.

D-INFK Gitlab service

This is the Gitlab service at the **Departement of Computer Science** of **ETH Zurich**

Besides the **in-line documentation**, there is a short **service documentation** with specifics like importing from our subversion service.

For support please write an email to support@inf.ethz.ch

Explore Help About GitLab

Sign in



NETHZ Standard

NETHZ Login


Password

Remember me

Sign in

Sign in with  

Create a repository



Create a repository

New Project · GitLab

https://gitlab.inf.ethz.ch/projects/new

Projects

New project

Create or Import your project from popular Git services

Project path

https://gitlab.inf.ethz.ch/zistvan/

Project name

asl-fall16-project

Import project from

GitHub Bitbucket GitLab.com Google Code Fogbugz git Repo by URL

Project description (optional)

Description format **Project name must be "asl-fall16-project"**

Visibility Level (?)

Private
Project access must be granted explicitly to each user.

Internal
The project can be cloned by any logged in user.

Public
The project can be cloned without any authentication.

Some visibility level settings have been restricted by the administrator.

Create project

Cancel

Create a repository

The screenshot shows a web browser window displaying the GitLab interface for a newly created repository. The browser's address bar shows the URL `https://gitlab.inf.ethz.ch/zistvan/asl-fall16-project`. The page header includes the user name 'Zsolt Istvan / asl-fall16-project' and a search bar. A blue notification banner at the top states 'Project 'asl-fall16-project' was successfully created.' Below this, the repository name 'asl-fall16-project' is displayed with a circular avatar containing the letter 'A'. A dropdown menu is open, showing options: 'Members', 'Groups', 'Deploy Keys', 'Webhooks', 'Services', 'Protected Branches', and 'Edit Project'. The 'Members' option is highlighted with a red box. Below the repository name, there are buttons for 'Star' (0), 'HTTPS' protocol, and the repository URL `https://gitlab.inf.ethz.ch/zis`. The main content area features a message: 'The repository for this project is empty. If you already have files you can push them using command line instructions below. Otherwise you can start with adding a [README](#), a [LICENSE](#), or a [.gitignore](#) to this project.'

Command line instructions

Git global setup

```
git config --global user.name "Zsolt Istvan"
git config --global user.email "zsolt.istvan@inf.ethz.ch"
```

Create a new repository

```
git clone https://gitlab.inf.ethz.ch/zistvan/asl-fall16-project.git
cd asl-fall16-project
```

Create a repository

Members · Zsolt Istvan / asl-fall16-project · GitLab · Mozilla Firefox

Members · Zsolt Istvan / a...

https://gitlab.inf.ethz.ch/zistvan/asl-fall16-project/project_members

Zsolt Istvan / asl-fall16-project

This project Search

Project Activity

Add new user to project Import members

Users with access to this project are listed below.

People × Kaan Kara

Search for users by name, username, or email, or invite new ones using their email address.

Project Access Reporter

Read more about role permissions [here](#)

Access expiration date Select access expiration date

On this date, the user(s) will automatically lose access to this project.

Add users to project

asl-fall16-project project members 1

Find existing member by name

Zsolt Istvan zistvan It's you

Joined less than a minute ago Master

kkara
mewaida
zistvan
claudieb
dasidler


Add all of us to the
project as “Reporter”,
so that we can check
out the code.

Once the repository has been created...

- Send an email to your TA (find him on the website) with subject “**ASL Azure Voucher**”
- First line: **your short nethz login**
- Second line: **your microsoft email address on which you want the voucher**

After you sent this email, you will get an automated response on the MS account; follow instructions there.

Since we will enter your details by hand, this might take 1-2 days.



zistvan
myaddress@outlook.com

Installing memcached and memaslap

Required software on Azure VMs

```
echo "Install build tools and memcached"
```

```
sudo apt-get install build-essential libevent-dev memcached
```

```
echo "Get and build memaslap (will take a while)"
```

```
#use exactly this version of libmemcached!
```

```
wget https://launchpad.net/libmemcached/1.0/1.0.18/+download/libmemcached-1.0.18.tar.gz
```

```
tar xvf libmemcached-1.0.18.tar.gz
```

```
cd libmemcached-1.0.18
```

```
export LDFLAGS=-lpthread
```

```
./configure --enable-memaslap && make clients/memaslap
```

Remarks on memcached and memaslap

- Installing memcached should be fast. Once installed, start it with:

```
memcached -p 11212 -t 1
```

- Run it with 1 thread (this is the default setup for all experiments)
- Building memaslap will take minutes, so we recommend building it once, and then scp'ing it to new machines.

- To start the clients use (in clients/):

```
./memaslap -s <server>:11212 -T 64 -c 64 -o1 -S 1s -t <time> -F <workloadconfig>
```

- We will provide you with example configuration files (define read-write mix and value size), and you can create your own quite easily.
- Pipe output to a text file so that you can plot throughput, response times later
- For more info: <http://docs.libmemcached.org/bin/memaslap.html>

Bash Tutorial

Comments from previous years

- “I had to stay up all night to run experiments!”
- “I cannot work on this from home...”
- “It took us more than 40hr./week to work on this milestone.”
- Solution is simple

Automate the experiments!

Bash Basics

- Bash is the command line interface used by most Linux systems
- On Windows: Use Putty to connect to a remote machine
- Most Bash-commands are simple programs that are executed
- Recommended for automating experiments
 - Feel free to use other scripting languages (Python, ...)

Running Bash Commands

```
command arg1 arg2
```

starts a command prompt returns as soon as the command finished

```
command arg1 arg2 &
```

runs the command in the background

```
command arg1 arg2 > out
```

runs the command, write standard out to file called "out"

```
command arg1 arg2 | command2 arg
```

runs the command and "pipes" the output into command2

Conditionals in Bash

```
MYVAR=foo
# set variable MYVAR to foo
export MYVAR=bar
# set MYVAR, child processes will see it as well
if [ $MYVAR = foo ]
then
    echo "MYVAR is foo"
elif [ $MYVAR = bar]
then
    echo "Bar"
else
    echo "Somethingisodd"
fi
```


Loops in Bash

```
for i in $(ls)
do
    echo item:$i
done
```

```
for i in `seq 1 10`
do
    echo $i
done
```

```
COUNTER=0
while [ $COUNTER -lt 10]
do
    echo The counter is $COUNTER
    let COUNTER=COUNTER+1
done
```

Running across multiple machines

- Use SSH and SCP
 - `ssh darkoma@optimus.ethz.ch`
 - Login to machine called `optimus.ethz.ch` as user `darkoma`
 - `ssh darkoma@optimus.ethz.ch "ls"`
 - Execute command `"ls"` on `optimus` as user `darkoma`
 - This is great for scripting!!!
 - `scp project.jar darkoma@optimus.ethz.ch:~/asl`
 - Copy `project.jar` to `~/asl` on `optimus`
- Hints:
 - To use `ssh` and `scp` in scripts use public key for passwordless authentication
 - Use `ssh -i <some-key>` to use a different key-pair from your default one

Enabling Passwordless Login

- To enable passwordless login on local machine:

```
cat ~/.ssh/id_rsa.pub >>  
~/.ssh/authorized_keys
```

- To enable passwordless login on remote machine:

```
ssh-copy-id <username>@<machine>
```

- If there is no id_rsa.pub:

```
ssh-keygen
```


- And don't give a password

ASL – Fall 2016


Gitlab, SW setup + Bash

Gitlab account and permissions

Create a repository



Create a repository



Create a repository

New Project - GitLab

Projects

New project

Create or Import your project from popular Git services

Project path

Project name

Project path: `https://gitlab.inf.ethz.ch/zistvan/`

Project name: `asl-fall16-project`

Import project from

Project description (optional)

Description format

Project name must be "asl-fall16-project"

Visibility Level (?)

- Private
Project access must be granted explicitly to each user.
- Internal
The project can be cloned by any logged in user.
- Public
The project can be cloned without any authentication.

Some visibility level settings have been restricted by the administrator.

Create project

Cancel

Create a repository


The screenshot shows a web browser window displaying the GitLab interface for a newly created repository named 'asl-fall16-project'. The browser's address bar shows the URL 'https://gitlab.inf.ethz.ch/zsoltvan/asl-fall16-project'. The page header includes the user 'Zsolt Istvan / asl-fall16-project' and a search bar. A blue notification banner at the top states 'Project 'asl-fall16-project' was successfully created.' Below this, the repository name 'asl-fall16-project' is displayed with a star icon and a count of 0. A dropdown menu is open on the right side of the repository name, listing options: Members, Groups, Deploy Keys, Webhooks, Services, Protected Branches, and Edit Project. The main content area features a message: 'The repository for this project is empty. If you already have files you can push them using command line instructions below. Otherwise you can start with adding a README, a LICENSE, or a .gitignore to this project.' Underneath, there are two sections for 'Command line instructions'. The first section, 'Git global setup', contains the following code:

```
git config --global user.name "Zsolt Istvan"
git config --global user.email "zsolt.istvan@inf.ethz.ch"
```

 The second section, 'Create a new repository', contains the following code:

```
git clone https://gitlab.inf.ethz.ch/zsoltvan/asl-fall16-project.git
```

Create a repository




kkara
mewaida
zistvan
claudieb
dasidler

Add all of us to the
project as "Reporter",
so that we can check
out the code.

Once the repository has been created...

- Send an email to your TA (find him on the website) with subject “**ASL Azure Voucher**”
- First line: **your short nethz login**
- Second line: **your microsoft email address on which you want the voucher**

After you sent this email, you will get an automated response on the MS account; follow instructions there. Since we will enter your details by hand, this might take 1-2 days.



Installing memcached and memaslap

Required software on Azure VMs

```
echo "Install build tools and memcached"

sudo apt-get install build-essential libevent-dev memcached

echo "Get and build memaslap (will take a while)"

#use exactly this version of libmemcached!

wget https://launchpad.net/libmemcached/1.0/1.0.18/+download/libmemcached-1.0.18.tar.gz

tar xvf libmemcached-1.0.18.tar.gz

cd libmemcached-1.0.18

export LDFLAGS=-lpthread

./configure --enable-memaslap && make clients/memaslap
```

Remarks on memcached and memaslap

- Installing memcached should be fast. Once installed, start it with:

```
memcached -p 11212 -t 1
```

- Run it with 1 thread (this is the default setup for all experiments)
- Building memaslap will take minutes, so we recommend building it once, and then scp'ing it to new machines.
 - To start the clients use (in clients/):

```
./memaslap -s <server>:11212 -T 64 -c 64 -o1 -S 1s -t <time> -F <workloadconfig>
```
 - We will provide you with example configuration files (define read-write mix and value size), and you can create your own quite easily.
 - Pipe output to a text file so that you can plot throughput, response times later
 - For more info: <http://docs.libmemcached.org/bin/memaslap.html>

Bash Tutorial

Comments from previous years

- “I had to stay up all night to run experiments!”
- “I cannot work on this from home...”
- “It took us more than 40hr./week to work on this milestone.”
- Solution is simple

Automate the experiments!

Bash Basics

- Bash is the command line interface used by most Linux systems
- On Windows: Use Putty to connect to a remote machine
- Most Bash-commands are simple programs that are executed
- Recommended for automating experiments
 - Feel free to use other scripting languages (Python, ...)

Running Bash Commands

```
command arg1 arg2
```

```
# starts a command prompt returns as soon as the command finished
```

```
command arg1 arg2 &
```

```
# runs the command in the background
```

```
command arg1 arg2 > out
```

```
# runs the command, write standard out to file called "out"
```

```
command arg1 arg2 | command2 arg
```

```
# runs the command and "pipes" the output into command2
```

Conditionals in Bash

```
MYVAR=foo
# set variable MYVAR to foo
export MYVAR=bar
# set MYVAR, child processes will see it as well
if [ $MYVAR = foo ]
then
    echo "MYVAR is foo"
elif [ $MYVAR = bar]
then
    echo "Bar"
else
    echo "Somethingisodd"
fi
```

Loops in Bash

```
for i in $(ls)
do
    echo item:$i
done

for i in `seq 1 10`
do
    echo $i
done

COUNTER=0
while [ $COUNTER -lt 10]
do
    echo The counter is $COUNTER
    let COUNTER=COUNTER+1
done
```

Running across multiple machines

- Use SSH and SCP

- `ssh darkoma@optimus.ethz.ch`
 - Login to machine called `optimus.ethz.ch` as user `darkoma`
- `ssh darkoma@optimus.ethz.ch "ls"`
 - Execute command `"ls"` on `optimus` as user `darkoma`
 - This is great for scripting!!!
- `scp project.jar darkoma@optimus.ethz.ch:~/asl`
 - Copy `project.jar` to `~/asl` on `optimus`

- Hints:

- To use `ssh` and `scp` in scripts use public key for passwordless authentication
- Use `ssh -i <some-key>` to use a different key-pair from your default one

Enabling Passwordless Login

- To enable passwordless login on local machine:

```
cat ~/.ssh/id_rsa.pub >>  
~/.ssh/authorized_keys
```

- To enable passwordless login on remote machine:

```
ssh-copy-id <username>@<machine>
```

- If there is no id_rsa.pub:

```
ssh-keygen
```

- And don't give a password